

Cilindro de Seguridad de perfil europeo



STS MEGA6

Características:

- Sistema de Seguridad.
- 6 Pitones activos de alpaca.
- Llave plana reversible de latón Niquelada.
- Media capacidad de amaestramiento.

DOBLES	L	A	B	LATÓN	€	NIQUEL	€	
	60	30	30	ME6EU53030L		ME6EU53030N		
	65	30	35	ME6EU53035L		ME6EU53035N		
	70	30	40	ME6EU53040L		ME6EU53040N		
		35	35	ME6EU53535L		ME6EU53535N		
	80	30	50	ME6EU53050L		ME6EU53050N		
		40	40	ME6EU54040L		ME6EU54040N		
	90	30	60	ME6EU53060L		ME6EU53060N		
		40	50	ME6EU54050L		ME6EU54050N		
		45	45	ME6EU54545L		ME6EU54545N		
	100	30	70	ME6EU53070L		ME6EU53070N		
		40	60	ME6EU54060L		ME6EU54060N		
		50	50	ME6EU55050L		ME6EU55050N		
	110	30	80	ME6EU53080L		ME6EU53080N		
		40	70	ME6EU54070L		ME6EU54070N		
		50	60	ME6EU55060L		ME6EU55060N		
	120	30	90	ME6EU53090L		ME6EU53090N		
40		80	ME6EU54080L		ME6EU54080N			
50		70	ME6EU55070L		ME6EU55070N			
60		60	ME6EU56060L		ME6EU56060N			
MEDIOS	40	30	10	ME6EU53010L		ME6EU53010N		
	45	35	10	ME6EU53510L		ME6EU53510N		
	50	40	10	ME6EU54010L		ME6EU54010N		
	60	50	10	ME6EU55010L		ME6EU55010N		
	70	60	10	ME6EU56010L		ME6EU56010N		
	80	70	10	ME6EU57010L		ME6EU57010N		
	90	80	10	ME6EU58010L		ME6EU58010N		
	100	90	10	ME6EU59010L		ME6EU59010N		
	BOTON	60	30	30	ME6EUB3030L		ME6EUB3030N	
		65	30	35	ME6EUB3035L		ME6EUB3035N	
		70	30	40	ME6EUB3040L		ME6EUB3040N	
35			35	ME6EUB3535L		ME6EUB3535N		
80		30	50	ME6EUB3050L		ME6EUB3050N		
		40	40	ME6EUB4040L		ME6EUB4040N		
90		30	60	ME6EUB3060L		ME6EUB3060N		
		45	45	ME6EUB4545L		ME6EUB4545N		
	40	30	10	ME6EURL		ME6EURN		
	40	30	10	ME6EUR2520L		ME6EUR2520N		

* Para otras dimensiones consultar.
 * Para otras levas corta (R13) ó dentadas (Z) consultar.
 (1) Medidas disponibles en breve con sistema modular. Consultar